

2661
tl 6
02-25-02



S/N 09/825898

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Longoni	Examiner:	To be assigned
Serial No.:	09/825898	Group Art Unit:	2661
Filed:	4/4/01	Docket No.:	975.330USW1
Title:	FRAME CONTROL METHOD AND APPARATUS		

CERTIFICATE UNDER 37 C.F.R. 1.8: The undersigned hereby certifies that this Transmittal Letter and the paper, as described herein, are being deposited in the United States Postal Service, as first class mail, with sufficient postage, in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C. 20231 on November 30, 2001

Michael B. Lasky
Name

[Signature]
Signature

RECEIVED

JAN 23 2002

Technology Center 2600

Box
Assistant Commissioner for Patents
Washington, D.C. 20231

- ☒ Certified copy of EP application, Serial Number PCT/EP98/06334, filed 5 October 1998; Submission of Priority Document
- ☒ Transmittal Sheet
- ☒ Return postcard

Authorization is hereby given to charge any additional fees or credit any overpayments that may be deemed necessary to Deposit Account Number 50-1038.

Respectfully submitted,

Altera Law Group, LLC
6500 City West Parkway – Suite 100
Minneapolis, MN 55344-7701
952-912-0527

Date: November 30, 2001

By:

[Signature]
Michael B. Lasky
Reg. No. 29,555
MBL/blj



S/N 09/825898

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	Longoni	Examiner:	To be assigned
Serial No.:	09/825898	Group Art Unit:	2661
Filed:	4/4/01	Docket No.:	975.330USW1
Title:	FRAME CONTROL METHOD AND APPARATUS		

CERTIFICATE OF MAILING UNDER 37 C.F.R. §1.8

I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, DC 20231 on November 30, 2001.

Michael B. Lasky

Name

Signature

SUBMISSION OF PRIORITY DOCUMENT

Box
Assistant Commissioner for Patents
Washington, D.C. 20231

Dear Sir:

Enclosed is a certified copy of EP application, Serial Number PCT/EP98/06334,
filed 5 October 1998, the priority of which is claimed under 35 U.S.C. §120.

Respectfully submitted,

Altera Law Group, LLC
6500 City West Parkway – Suite 100
Minneapolis, MN 55344-7701
952-912-0527

Date: November 30, 2001

By:

Michael B. Lasky
Reg. No. 29,555
MBL/blj



RECEIVED

JAN 23 2002

Technology Center 2600



Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten internationalen Patentanmeldung überein.

The attached documents are exact copies of the international patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet international spécifiée à la page suivante.

Den Haag, den
The Hague,
La Haye, le

09. 11. 2001

Der Präsident des Europäischen Patentamts
Im Auftrag
For the President of the European Patent Office
Le Président de l'Office européen des brevets
p. o.


Cocky van Amstel

Patentanmeldung Nr.
Patent application no. PCT/EP 98/06334
Demande de brevet n°



Anmeldung Nr.: PCT/EP 98/06334
Application no.:
Demande n°:

Anmelder: 1. NOKIA TELECOMMUNICATIONS OY - Nokia Group, Finland
Applicant(s): 2. Longoni, Fabio - Espoo, Finland
Demandeur(s):

Bezeichnung der Erfindung:
Title of the invention: Frame control method and apparatus
Titre de l'invention:

Anmeldetag:
Date of filing: 05 October 1998(05.10.98)
Date de dépôt:

In Anspruch genommene Priorität(en)
Priority(ies) claimed
Priorité(s) revendiquée(s)

Staat:	Tag:	Aktenzeichen:
State:	Date:	File no.
Pays:	Date:	Numéro de dépôt:

Benennung von Vertragsstaaten : Siehe Formblatt PCT/RO/101 (beigefügt)
Designation of contracting states : See Form PCT/RO/101 (enclosed)
Désignation d'états contractants : Voir Formulaire PCT/RO/101 (ci-joint)

Bemerkungen:
Remarks:
Remarques:

Feld Nr. V BESTIMMUNG VON STAATEN

Die folgenden Bestimmungen nach Regel 4.9 Absatz a werden hiermit vorgenommen (bitte die entsprechenden Kästchen ankreuzen; wenigstens ein Kästchen muß angekreuzt werden):

Regionales Patent

- ☒ AP **ARIPO-Patent:** GH Ghana, GM Gambia, KE Kenia, LS Lesotho, MW Malawi, SD Sudan, SZ Swasiland, UG Uganda, ZW Simbabwe und jeder weitere Staat, der Vertragsstaat des Harare-Protokolls und des PCT ist
- ☒ EA **Eurasisches Patent:** AM Armenien, AZ Aserbaidschan, BY Belarus, KG Kirgisistan, KZ Kasachstan, MD Republik Moldau, RU Russische Föderation, TJ Tadschikistan, TM Turkmenistan und jeder weitere Staat, der Vertragsstaat des Eurasischen Patentübereinkommens und des PCT ist
- ☒ EP **Europäisches Patent:** AT Österreich, BE Belgien, CH und LI Schweiz und Liechtenstein, CY Zypern, DE Deutschland, DK Dänemark, ES Spanien, FI Finnland, FR Frankreich, GB Vereinigtes Königreich, GR Griechenland, IE Irland, IT Italien, LU Luxemburg, MC Monaco, NL Niederlande, PT Portugal, SE Schweden und jeder weitere Staat, der Vertragsstaat des Europäischen Patentübereinkommens und des PCT ist
- ☒ OA **OAPI-Patent:** BF Burkina Faso, BJ Benin, CF Zentralafrikanische Republik, CG Kongo, CI Côte d'Ivoire, CM Kamerun, GA Gabun, GN Guinea, ML Mali, MR Mauretanien, NE Niger, SN Senegal, TD Tschad, TG Togo und jeder weitere Staat, der Vertragsstaat der OAPI und des PCT ist (falls eine andere Schutzrechtsart oder ein sonstiges Verfahren gewünscht wird, bitte auf der gepunkteten Linie angeben) **GW Guinea-Bissau**

Nationales Patent (falls eine andere Schutzrechtsart oder ein sonstiges Verfahren gewünscht wird, bitte auf der gepunkteten Linie angeben):

- | | |
|--|--|
| <input checked="" type="checkbox"/> AL Albanien | <input checked="" type="checkbox"/> LS Lesotho |
| <input checked="" type="checkbox"/> AM Armenien | <input checked="" type="checkbox"/> LT Litauen |
| <input checked="" type="checkbox"/> AT Österreich | <input checked="" type="checkbox"/> LU Luxemburg |
| <input checked="" type="checkbox"/> AU Australien | <input checked="" type="checkbox"/> LV Lettland |
| <input checked="" type="checkbox"/> AZ Aserbaidschan | <input checked="" type="checkbox"/> MD Republik Moldau |
| <input checked="" type="checkbox"/> BA Bosnien-Herzegowina | <input checked="" type="checkbox"/> MG Madagaskar |
| <input checked="" type="checkbox"/> BB Barbados | <input checked="" type="checkbox"/> MK Die ehemalige jugoslawische Republik Mazedonien |
| <input checked="" type="checkbox"/> BG Bulgarien | <input checked="" type="checkbox"/> MN Mongolei |
| <input checked="" type="checkbox"/> BR Brasilien | <input checked="" type="checkbox"/> MW Malawi |
| <input checked="" type="checkbox"/> BY Belarus | <input checked="" type="checkbox"/> MX Mexiko |
| <input checked="" type="checkbox"/> CA Kanada | <input checked="" type="checkbox"/> NO Norwegen |
| <input checked="" type="checkbox"/> CH und LI Schweiz und Liechtenstein | <input checked="" type="checkbox"/> NZ Neuseeland |
| <input checked="" type="checkbox"/> CN China | <input checked="" type="checkbox"/> PL Polen |
| <input checked="" type="checkbox"/> CU Kuba | <input checked="" type="checkbox"/> PT Portugal |
| <input checked="" type="checkbox"/> CZ Tschechische Republik | <input checked="" type="checkbox"/> RO Rumänien |
| <input checked="" type="checkbox"/> DE Deutschland | <input checked="" type="checkbox"/> RU Russische Föderation |
| <input checked="" type="checkbox"/> DK Dänemark | <input checked="" type="checkbox"/> SD Sudan |
| <input checked="" type="checkbox"/> EE Estland | <input checked="" type="checkbox"/> SE Schweden |
| <input checked="" type="checkbox"/> ES Spanien | <input checked="" type="checkbox"/> SG Singapur |
| <input checked="" type="checkbox"/> FI Finnland | <input checked="" type="checkbox"/> SI Slowenien |
| <input checked="" type="checkbox"/> GB Vereinigtes Königreich | <input checked="" type="checkbox"/> SK Slowakei |
| <input checked="" type="checkbox"/> GE Georgien | <input checked="" type="checkbox"/> SL Sierra Leone |
| <input checked="" type="checkbox"/> GH Ghana | <input checked="" type="checkbox"/> TJ Tadschikistan |
| <input checked="" type="checkbox"/> GM Gambia | <input checked="" type="checkbox"/> TM Turkmenistan |
| <input checked="" type="checkbox"/> GW Guinea-Bissau | <input checked="" type="checkbox"/> TR Türkei |
| <input checked="" type="checkbox"/> HR Kroatien | <input checked="" type="checkbox"/> TT Trinidad und Tobago |
| <input checked="" type="checkbox"/> HU Ungarn | <input checked="" type="checkbox"/> UA Ukraine |
| <input checked="" type="checkbox"/> ID Indonesien | <input checked="" type="checkbox"/> UG Uganda |
| <input checked="" type="checkbox"/> IL Israel | <input checked="" type="checkbox"/> US Vereinigte Staaten von Amerika |
| <input checked="" type="checkbox"/> IS Island | |
| <input checked="" type="checkbox"/> JP Japan | <input checked="" type="checkbox"/> UZ Usbekistan |
| <input checked="" type="checkbox"/> KE Kenia | <input checked="" type="checkbox"/> VN Vietnam |
| <input checked="" type="checkbox"/> KG Kirgisistan | <input checked="" type="checkbox"/> YU Jugoslawien |
| <input checked="" type="checkbox"/> KP Demokratische Volksrepublik Korea | <input checked="" type="checkbox"/> ZW Simbabwe |
| <input checked="" type="checkbox"/> KR Republik Korea | |
| <input checked="" type="checkbox"/> KZ Kasachstan | |
| <input checked="" type="checkbox"/> LC Saint Lucia | |
| <input checked="" type="checkbox"/> LK Sri Lanka | <input checked="" type="checkbox"/> GD Grenada |
| <input checked="" type="checkbox"/> LR Liberia | <input type="checkbox"/> |

Kästchen für die Bestimmung von Staaten (für die Zwecke eines nationalen Patents), die dem PCT nach der Veröffentlichung dieses Formblatts beigetreten sind:

Erklärung bzgl. vorsorglicher Bestimmungen: Zusätzlich zu den oben genannten Bestimmungen nimmt der Anmelder nach Regel 4.9 Absatz b auch alle anderen nach dem PCT zulässigen Bestimmungen vor mit Ausnahme der im Zusatzfeld genannten Bestimmungen, die von dieser Erklärung ausgenommen sind. Der Anmelder erklärt, daß diese zusätzlichen Bestimmungen unter dem Vorbehalt einer Bestätigung stehen und jede zusätzliche Bestimmung, die vor Ablauf von 15 Monaten ab dem Prioritätsdatum nicht bestätigt wurde, nach Ablauf dieser Frist als vom Anmelder zurückgenommen gilt. (Die Bestätigung einer Bestimmung erfolgt durch die Einreichung einer Mitteilung, in der diese Bestimmung angegeben wird, und die Zahlung der Bestimmungs- und der Bestätigungsgebühr. Die Bestätigung muß beim Anmeldeamt innerhalb der Frist von 15 Monaten eingehen.)

Frame control method and apparatus5 FIELD OF THE INVENTION

The present invention relates to a frame control method and apparatus for controlling a transport frame used for transmitting a data block via a dedicated channel between
10 network elements of a communication system having different types of connections, such as a WCDMA (Wideband Code Division Multiple Access) system for the UMTS (Universal Mobile Telecommunications System).

15 BACKGROUND OF THE INVENTION

Third generation mobile telecommunications systems aim at providing end-users, apart from terminal and personal mobility, with enhanced services. Compared to second
20 generation systems, enhancements that will cover features all the way between the end-user and the core network elements are required, i. e. from mobile terminals to radio access and fixed networks. The UMTS is such a third generation system, wherein, for example, Asynchronous
25 Transfer Mode (ATM) technologies may be selected so as to represent a business environment and support fixed ATM terminals.

Delivering wide band multimedia services will require
30 additional performance compared with today's wireless standards. In this respect, research has been conducted focusing on WCDMA which fully supports both packet- and circuit-switched communications such as Internet browsing and land line telephone services, respectively.

35 WCDMA is based on a modern, layered network-protocol structure similar to the protocol structure used in, for instance, GSM networks. This will facilitate the development of new wireless wide band multimedia
40 applications. With increasing demand for next-generation

- 2 -

mobile telephone services, there will be a new set of requirements on a wireless systems, such as:

- support for high speed data communication;
- 5 • support for both packet- and circuit-switched services, such as internet traffic and video conferencing;
- higher network capacity, better usage of the frequency spectrum, each user will require more capacity compared to today's voice services;
- 10 • support for several connections.

Users will, for instance, be able to browse the Internet in parallel to voice calls and/or video conferencing.

- 15 Recently, the European Telecommunications Standards Institute (ETSI) decided on WCDMA as the radio technology for the paired bands of the UMTS. The same applies to the standardization bodies of Japan and the USA. Consequently, WCDMA is the common radio technology standard for third-
- 20 generation wide-area mobile communications in Europe, North America and Asia.

- The WCDMA concept is based on a totally new channel structure for all layers (L1 to L3) build on technologies
- 25 such as packet-data channels and service multiplexing. The new concept also includes pilot symbols and a time-slotted structure.

- In practice, certain key parameters in WCDMA and GSM have
- 30 been harmonized in order to achieve an optimum solution for dual-mode GSM/UMTS terminals as well as GSM/UMTS hand-over. This will facilitate today's users easy access to third-generation services through dual-mode terminals, as will be the case with UMTS/GSM terminals.

35

In WCDMA systems, user plane data entities (in the following referred to as transport blocks TB) need to be transported between a radio network controller (RNC) and a

- 3 -

base station (BS) of a mobile network like the GSM network. A frame layer control protocol exists that handles the transmission between the above two network elements (BS and RNC), which is referred to as Radio Block Transport
5 Protocol (RBTP) in the following.

The RBTP is adapted to attach to a transport block TB all information which the layers 2/3 in the RNC and the layer 1 in the BS need to exchange. This information is necessary
10 for synchronization (e.g. a frame number to synchronize the transmission), outer loop PC (e.g. a frame reliability information and a power control command), macro diversity combining (e.g. a system frame number and the L1 cyclic redundancy check), indication of L1 processing to be done
15 (e.g. a transport format indicator TFI), and identification of a channel to which the present TB belongs.

According to a known solution, a fixed structure of the RBTP frame for one kind of channel is used, e.g. there is
20 one structure for a dedicated channel with a fixed number of bit reserved for every field.

However, the parameters necessary to be attached to the TB are different for different kind of transport channels that
25 the WCDMA system supports (e.g. common channels, dedicated channel with and without soft handover possibility, high and low bit rate, fixed or variable bit rate, best effort packet data channels), because the nature of the channels and the characteristic of the data transmitted over them
30 are different.

Therefore, the above known solution leads to the drawback that the transmission link is not efficiently used, since the RBTP frame may contain information which is not
35 necessary or which can be specified with a minor number of bits, due to the specific characteristic of the channel.

SUMMARY OF THE INVENTION

It is therefore an object of the present invention to provide a frame control method and apparatus which allow
5 flexibility and minimum usage of the transmission link capacity.

This object is achieved by a frame control method for controlling a transport frame used for transmitting a data
10 unit via a dedicated channel between network elements of a communication system having different types of connections, comprising the steps of:
encapsulating a data unit into said transport frame; and
selecting a frame type coding of said transport frame in
15 accordance with a connection type of said dedicated channel.

Additionally, this object is achieved by a frame control apparatus for controlling a transport frame used for
20 transmitting a data unit via a dedicated channel between network elements of a communication system having different types of connections, comprising:
means for encapsulating said data unit into said transport frame; and
25 means for selecting a frame type coding of said transport frame in accordance with a connection type of said dedicated channel.

Accordingly, an adaptive frame type coding is provided,
30 which allows a very efficient usage of the transmission resources between the network elements, whereby the overhead of the control information for the transmission of the user data is reduced to a minimum. Moreover, the memory required to buffer the user data in the network elements is
35 reduced. This benefit is of particular advantage in WCDMA systems, because dedicated channels with a wide range of characteristics are provided therein, and the usage of a common structure for the transport leads to a high protocol

- 5 -

overhead, particularly for speech channels. Nevertheless, the above solution can be used in any communication system having different types of connections.

- 5 In view of the fact that a minimum control information is used, processing capacity can be reduced, since the decoding processing requires less processing capacity.

10 Preferably, the frame type coding defines specific control information fields of the transport frame and their bit number. Thus, unnecessary control information fields which are not required for specific connection types of a dedicated channel can be canceled or at least their bit number can be reduced, so as to reduce the overhead of the control information. In particular, the bit number of a transport format indicator field can be determined on the basis of the number of different transport format indicators allowed for a dedicated channel.

20 Furthermore, the value of the transport format indicator field may define if and how a whole original data unit is split into different data units to be transported via the dedicated channel. Thereby, a segmentation of a transport data block may be performed, if its dimension exceeds the maximum dimension allowed by the underlying transport mechanism of the connection type of the dedicated channel.

30 Moreover, the value of the transport format indicator field may define the presence and/or bit number of another one of said specific control information fields. Thereby, a specific control information relating to the transport format of the connection can be added or adapted. Such a specific control information may be a frame reliability information required for high bit rate transmissions in order to improve quality control.

The coding format may be selected in a set-up phase of the dedicated channel based on corresponding set-up parameters

- 6 -

of the dedicated channel. Thus, the structure of the transport frame readily can be changed when a change of the channel parameters of the dedicated channel has been detected.

5

In case only one transport connection is allocated to the dedicated channel, a channel indicator field may be deleted from the control information, since the network elements at the receiving and the transmitting end already know the type of connection, such that the frame type can be decoded at the receiving end using both the information concerning the connection type and the short frame information code provided in a transport frame itself.

10

15 The frame control method preferably may be used in a user plane interface of a WCDMA system. The dedicated channel may be an ATM AAL2 channel, wherein the data unit may be a user plane data unit.

20

In case the frame control method is used in a mobile communication system, such as the GSM system, the network elements may comprise a base station and a radio network controller.

25

BRIEF DESCRIPTION OF THE DRAWINGS

In the following the present invention will be described in greater detail on the bases of a preferred embodiment with reference to the accompanying drawings in which:

30

Fig. 1 shows a block diagram of a mobile communication system connected to different network types in order to deliver multimedia services,

35

Fig. 2 shows a principle diagram of a transport frame used in the frame control method according to the present invention, and

- 7 -

Fig. 3 shows a principle block diagram of a network element comprising a frame control apparatus according to the preferred embodiment of the invention.

5 DESCRIPTION OF THE PREFERRED EMBODIMENT

The following preferred embodiment relates to a frame control method used in a WCDMA system used in a mobile communication system.

10 According to Fig. 1, a mobile communication system 6 comprises a mobile station (MS) 1 radio-connected to a base station subsystem (BSS) 2. The BSS 2 is connected to a radio network controller (RNC) 3 which may be connected to
15 a circuit-switched network like a Public Switched Telephone Network (PSTN) 4 and to a packet-switched network like the Internet 5.

20 The WCDMA system enables a full support of both packet- and circuit-switched communications.

 In the WCDMA system according to the preferred embodiment, the RBTP is used to adapt the UMTS user plane interfaces Iur and Iub between the RNC 3 and the BSS 2. In particular,
25 the RBTP is used to adapt the TB, i.e. a user plane data unit such as a MAC PDU (Media Access Control Packet Data Unit), to an AAL 2 channel (ATM Adaptation Layer type 2). In such a transmission, the type of the transport frame (RBTP frame) has to be indicated in each frame. However, in
30 at least most connection types only a small subset of the possible FCL frame types is used. The TBs (MAC PDUs) are encapsulated by the RBTP in frames that contain all the relevant information which is to be exchanged between the BSS 2 and the RNC 3.

35 Fig. 2 shows an example for such a transport frame. According to Fig. 2, the transport frame consists of transport blocks TB and a control information portion CI

- 8 -

comprising a plurality of control information fields. The control information portion CI forms the head of the transport frame and is may be called "header" of the transport frame. The control information field CI is
5 followed by a plurality of transport blocks TB which correspond to the user plane data units (PDUs).

As indicated by the arrow in Fig. 2, the RBTP defines a connection type specific frame type coding of the transport
10 frame, wherein different bit rates and different natures of the dedicated transport channel (e.g. an AAL 2 link) are considered. In particular, the information fields of the control information portion CI of the transport frame and their bit numbers are selected in accordance with the
15 connection type of the dedicated transport channel.

Fig. 3 shows a principle diagram of a downlink or uplink part of a network element 10 such as the RNC 3 or a base station controller BSC of the BSS 2, respectively. The
20 network element 10 is arranged at one end of a transmission link such as the AAL2 connection. An input signal comprising TBs to be transmitted via the AAL2 connection is received by a receiving means 11 which extracts the TBs from the received input signal and supplies the extracted
25 TBs to a frame generating means 12. The frame generating means 12 encapsulates the supplied TBs in frames in accordance with the RBTP, so as to generate the RBTP frames to transmitted via the AAL2 connection.

30 Furthermore, a selecting means 13 is provided which receives from the receiving means 11 an information concerning the connection type of the dedicated transport channel. This connection type information may be derived from received parameters of the dedicated transport
35 channel. Based on the connection type information, the selecting means 13 selects a specific frame type coding and controls the frame generating means 12 so as to generate

- 9 -

the RBTP frames in accordance with the selected frame type coding.

The frame type coding can be selected in the set-up phase based on the parameters of the dedicated transport channel, and may be modified by the selecting means 13 when the parameters are changed. Moreover, in case different transport formats are used in the dedicated channel, the transport format currently used for a specific user plane data unit set may also specify if and how the whole user plane data unit set is split into different TBs of the RBTP. Optionally, the value of a transport format indicator (TFI) of the control information portion CI may also be used to determine the presence and bit number of other information fields in the control information portion and their bit numbers.

Thus, the frame type coding of the transport frame and particularly the length of the control information portion CI depends on the connection characteristic of the dedicated channel, in which they are used.

For example, the length in bit of a transport format indicator (TFI) field is given by the number of the different TFIs that are allowed for that channel. Moreover, as already said, the current TFI may define how a complete set of data units or transport blocks (i.e. the transport block set which is processed as a single entity by the OSI layer 1 of the BSS 2) is segmented (if necessary) into different transport frames. The segmentation of the TB may be required if its dimension exceeds the maximum dimension allowed by the underlying transport mechanism of the connecting type of the dedicated channel.

An additional frame reliability information field may be provided in the control information portion, if the TFI value indicates a high bit rate transmission via an established connection. Thereby, quality control of the

- 10 -

high bit rate transmission can be improved. However, in case the TFI value indicates a low bit rate transmission via the same connection, such a frame reliability information field is not provided in the control information portion.

In case one transport connection, such as the AAL 2 connection, is allocated to a dedicated channel, it is not necessary to provide a channel/sub-channel indicator in the transport frames, because the transmission resources dedicated for the specific channel are used.

In the following, examples for different dedicated channels and their corresponding frame type codings selected by the selecting means 13 are described:

A first dedicated channel DCH1 may be a speech channel with two transport formats relating to 4.8 kbit/s and 0 kbit/s (Discontinuous Transmission, DTX). In this case, each transport frame carries two transport blocks TB, transmitted in 20 ms, or no data (speechless period), and may be composed such that the TBs are provided with their Cyclic Redundancy Check (CRC) information or another reliability information. The control information portion CI comprises a frame number (N bits, constant as a system parameter), a TFI field of only one bit defining the two transport formats, i.e. speech or no speech, and all relevant outer loop PC information.

Furthermore, a second dedicated channel DCH2 may be provided, to which a CS variable rate connection with 16 different transport formats corresponding up to 256 kbit/s is allocated. Here, the structure of the transport frame corresponds to that of the DCH1, wherein the TFI field is composed of 4 bits the value of which determines how the whole transport block set is segmented. For example, TFI = 16 indicates three transport frames for every transport block set, wherein the structure of the second and third

- 11 -

frame is different from the structure of the first frame. In this case, it is not necessary to specify any frame number in the second and third frame.

- 5 Additionally, a third dedicated channel BCH3 may be provided for a unidirectional best effort packet data connection without macro diversity. In this case, the transport frame not necessarily requires all the fields related to the outer loop PC and a macrodiversity combiner
10 in the control information portion CI. However, if a common pipe is used to transport multiple dedicated channels of this type, the control information portion CI of the transport frame must include a channel identifier.
- 15 As can be gathered from the above description of the preferred embodiment, the frame type coding of the transport frame, i.e. fields and bit number per field of the control information portion CI, its dimension and segmentation, is defined for each connection type of the
20 dedicated channel, and may change when the channel parameters defining the connection type are changed. Thus, this connection type specific frame type coding requires less bits than the above mentioned traditional coding method, and transmission and processing capacity can be
25 saved.

It should be understood that the above description and accompanying drawings are only intending to illustrate the present invention. Thus, the frame control method and
30 apparatus according to the present invention may also be used in other communications systems having different types of connections. The preferred embodiment of the invention may vary within the scope of the attached claims.

- 35 A frame control method and apparatus is described for controlling a transport frame used for transmitting a data unit via a dedicated channel between network elements of a communication system having different types of connections.

- 12 -

The frame type coding of the transport frame is selected in accordance with a connection type of the dedicated channel, such that a connection type specific frame length, dimension and/or segmentation is achieved. This allows an efficient usage of transmission resources, wherein an overhead of control information for the transmission of the data units is minimized.

Claims

1. A frame control method for controlling a transport
5 frame used for transmitting a data unit (TB) via a
dedicated channel between network elements (2, 3; 10) of a
communication system having different types of connections,
comprising the steps of:
(a) encapsulating said data unit (TB) into said transport
10 frame; and
(b) selecting a frame type coding of said transport frame
in accordance with a connection type of said dedicated
channel.
- 15 2. A frame control method according to claim 1, wherein
said frame type coding defines specific control information
fields of the transport frame and its bit number.
- 20 3. A frame control method according to claim 2, wherein
said specific control information fields include a
transport format indicator field the bit number of which is
determined on the basis of the number of different
transport format indicators allowed for said dedicated
channel.
- 25 4. A frame control method according to claim 3, wherein
the value of said transport format indicator field defines
if and how a whole original data unit set is split into
different data units to be transported via said dedicated
30 channel.
5. A frame control method according to claim 3 or 4,
wherein the value of said transport format indicator field
defines the presence and/or bit number of another one of
35 said specific control information fields.
6. A frame control method according to claim 5, wherein
said other one of said specific control information fields


is a frame reliability information field which is provided when the value of said transport format indicator field indicates a high bit rate transmission.

- 5 7. A frame control method according to any one of the preceding claims, wherein said frame type coding is selected in a set-up phase of said dedicated channel based on corresponding set-up parameters of said dedicated channel.
- 10 8. A frame control method according to claim 1, wherein said frame type coding does not include a channel indicator field, if one transport connection is allocated to said dedicated channel.
- 15 9. A frame control method according to any one of the proceeding claims, wherein said frame control method is used in a user plane interface of a WCDMA system.
- 20 10. A frame control method according to claim 9, wherein said dedicated channel is an AAL 2 channel and said data unit is a user plane data unit.
- 25 11. A frame control apparatus for controlling a transport frame used for transmitting a data unit (TB) via a dedicated channel between network elements (2, 3; 10) of a communication system having different types of connections, comprising:
 - 30 (a) means (12) for encapsulating said data unit (TB) into said transport frame; and
 - (b) means (13) for selecting a frame type coding of said transport frame in accordance with a connection type of said dedicated channel.
- 35 12. A frame control apparatus according to claim 1, wherein said network elements (2, 3; 10) comprise a base station subsystem (2) and a radio network controller (3) of a mobile communication system (6).

Abstract:

A frame control method and apparatus is described for
5 controlling a transport frame used for transmitting a data
unit via a dedicated channel between network elements of a
communication system having different types of connections.
The frame type coding of the transport frame is selected in
accordance with a connection type of the dedicated channel,
10 such that a connection type specific frame length,
dimension and/or segmentation is achieved. This allows an
efficient usage of transmission resources, wherein an
overhead of control information for the transmission of the
data units is minimized.

15

**Fig. 1**




Fig. 2




Fig. 3